

	A	B	C	D	E	F	G	H
M/L	54.00	58.00	62.00	64.00	66.00	70.00	74.00	78.00
A/P	51.00	54.00	58.00	60.00	62.00	66.00	70.00	74.00

	1	2	3	4	5	6	7	8
M/L	59	62	66	66	71	72	76	78
A/P	40	40	42	46	48	50	52	54

		Femoral Component Size										
		A	B	C	D	E	F	G	H			
Metal Back Tibial Tray Size	1										<div>1/2</div> <div>3/4</div> <div>5/6</div> <div>7/8</div>	Thickness of Tibial Liner  9mm 11mm 14mm 17mm
	2											
	3											
	4											
	5											
	6											
	7											
	8											

		Femoral Component Size							
		A	B	C	D	E	F	G	H
All-poly Tibial Component size	A1								
	B2								
	C2								
	C3								
	D2								
	D3								
	D4								
	E4								
E5									
F5									
G7									

**maxx**  
medical

Taller bodies to increase contact area between instrument and distal face of femur for added stability

Sliding stylus to increase flexibility in sizing throughout range

Pin holes for additional fixation, if desired

Tightened fit between body and sizing post to increase stability

Threaded holes for inserting under condyles with handle and rod

Lower profile feet to slide under condyles more easily

Threaded hole to affix handle and rod if required

Posterior fixation holes

Slots for gap balancing technique

Threaded hole to affix stylus

Tightened holes and increased height to increase stability

Stylus threads into cutting block through anterior hole for added stability and precision

maxx [www.maxxmed.com](http://www.maxxmed.com)



**FREEDOM<sup>®</sup>**  
**KNEE**

- The one & only 7 radii knee implant in the world
- Optimised A-P & M-L ratios for femur & tibia
- Asymmetrical cam & spine mechanism for rotation up to 15 degree
- 6 degree deep trochlear groove
- Thin anterior flange
- Small femoral box profile
- Small femoral posterior condyle resection
- Extended 7<sup>th</sup> radii in the posterior condyle
- 5 point cobalt chrome tibial locking system with 3 degree & 30 mm keel
- Minimized surface roughness of 11 uin for tibial trays for superior finish
- Ram extruded poly UHMWPE, GUR 1020
- Modularity of sizes & compatibility




The one and only 7 radii femoral implant in the world:  
Facilitates coordinate articular geometry of natural femur

Coordinate articular geometry of the Freedom<sup>®</sup> femur 7 tangent radii ensures uniform load dissipation through optimised area contact

Radii 1, 2 and 3 ensure optimized patella-femoral contact.


They must be tightly controlled for smooth tracking over a thin anterior flange for optimized extensor mechanism & also minimizing the contact stress through uniform load dissipation.



Radii 4, 5, 6 and 7 control femoral rollback and flexion over a wide array of biomechanical requirements, from walking to climbing stairs & ensure optimized area contact for uniform load dissipation both in extension & flexion thereby minimizing the contact stress.


The Freedom Femoral design is based on functional principles of progressive multi-radii of Patello-femoral and Tibio-femoral contact areas

7 radii along with thin anterior flange and 6 degree deep trochlear groove facilitate predictable Patello-femoral tracking resulting in smooth extensor mechanism



Smooth extensor mechanism helps in reducing anterior knee pain.



Multi radii design for predictable femoral roll back and high flexion



Increased femoral roll back allowing high flexion up to 155 degree for various daily & social activities.


Asymmetrical post-cam mechanism for rotation at deep flexion

A modified post-cam mechanism allows for stability, posterior clearance and protection against subluxation during deep flexion.




Achieves rotation up to 15 degree at deep flexion to prevent post-cam impingement, thereby reducing wear and tear of poly.

Prevention of edge loading at deep flexion



Representative Surface Stress Distribution 15 - 40 + MPa at 90 Degree Flexion, 333 kgf Load




Representative Surface Stress Distribution 15 - 40+MPa at 135 Degree Flexion, 222 kgf Load

Freedom Knee concentrates loads towards the center of the poly.

Minimised micro motion in tibia

- 5 point locking mechanism and Optimized inside surface roughness average (11 uin).
- Minimizes micro motion in tibia, thus reducing the back side wear in the tibial tray thereby improving the durability of the implant.



Both Freedom<sup>™</sup> CR and PS Tibial Inserts have identical locking mechanisms to mate.

Intelligent design for bone conservation

Thin anterior flange, low profile box and multi-radii design for minimized posterior condylar resection results in maximum bone conservation.


Freedom Knee: Post condylar bone resection (mm)

A	B	C	D	E	F	G
7.2	7.7	8.2	8.5	8.8	9.4	9.8

Freedom Knee: Box cut bone resection (cm<sup>3</sup>)

A	B	C	D	E	F	G
4.37	5.42	6.44	7.14	7.91	9.69	11.26

Importance of design in increasing implant longevity/ durability



Source: White paper on comparative Lab Test Data on polywear characteristics